

Tradesman Machinist T6NC



Tradesman 6" Machinist NC (single shaft)
Grind anything: unlike any other grinder, you can grind carbide tools or Teflon on the same wheel. Our most compact grinder is great for many important machinist operations

- Weldon set screw flats
- Neck reduction
- Carbide and HSS cut off
- Lathe tools
- Carbide inserts
- Corner rads, carbide corner prep
- Reamers
- Unibits
- Countersinks
- Belt sander

Conventional grinders with conventional wheels don't grind carbide very well. Fifty percent of the effort, energy and torque in the grinding process is wasted in wheel wear and consumption --- and lots of noise. The Tradesman with Cuttermasters Precision Plated Superabrasive wheels is different. Flat and sharp grinding surface, great for shaping and sharpening and no bucket of water on the front. The patented Tradesman Low Speed High Feed Grinding system is balanced, smooth and quiet. With a low speed of 500 RPM, and no run out, there's nothing threatening about it.

Wheel diameter	6" or belt
Voltage	110V or 240V(opt.)
Frequency	60Hz
Rated power	400W
Wheel speed	500-4000 rpm
Height at 6" guard	9.25"
Width at 6" guards	10.8"
Depth of Base	8"
Wheel center height	5.5"
Shaft diameter	5/8", 1-1/4" hub
Shaft concentricity	.0002" (5µm)

Tradesman Machinist Accessories



T-ER32i
Necks, Flats, Cut Off, Rads



T-WF
V-Block for Flats and Cut Off



T-MRF
Micro Adjust Feed Rest

Engineering and Prototyping - 2353 Ridgcrest Place, Ottawa ON K1H 7V4
Manufacturing and Distribution - 808 Proctor Ave, Ogdensburg NY 13669
CALL US 1 (800) 417-2171

www.tradesmangrinder.com or email: cuttermaster@gmail.com

